

ELECTRIC PRESSURE WASHER COMMERCIAL HOT WATER WITH ALL COVERED FRAME

Dual layer steel coil construction and top fired burning design feature a high heat exchange. Equipment high performance DANFORSS fuel pump. Integral welded frame for better load bearing capability and components installation stability. Equipped with large 20L blow molded fuel tank. Smart control system controls the motor start and stop, and burning start and stop, and the temperature settings. Compact design suitable for frequency cleaning applications for manufacturing plants, food processing, catering, hotel, shopping malls and supermarkets and automobile cleaning.



BURNER Diesel Burning Firing System

Dual layer steel coil construction and top fired burning design to keep the heated air in the chamber longer to utilize the max amount of the heat for the air flow. Equipment high performance DANFORSS fuel pump.



FRAME Integral Frame

Integral welded frame for better load bearing capability and components installation stability. Equipped with large 20L blow molded fuel tank for longer single using time. Top and surround cover with ventilating cut out.



CONTROLLER Smart Temp. Controller

Controller system consists of flow, pressure, light and temperature sensor, and several controllers, that controls the motor start and stop, and burning start and stop, and the temperature settings.



PUMP Commercial Crankshaft Triplex Pump

Brass forged manifold with integrated unloader, built with high- low water seals, ceramic coating plunger. Steel forged crankshaft with multiple grinding processes. Enlarged crankcase built with oil sight glass.



MOTOR High Quality Induction Motor

High quality standard induction 4 pole motor, copper wire winding, features stable power output, less heat and less noise, for reliable and durable usage.



WHEEL Solid Wheel And Swivel Castor

2 x 10" Wheel with plastic wheel hub with wear-resistant hard plastic wheel rim, without bearing. None flat. 2 x 3.5" Swivel castor for better maneuverability and easy movement, castor build with brake.

| MODEL | DHAE-8/10-254 | DHAE-10/10-2.554 |
|-------------------------|----------------------------|----------------------------|
| Rated Flow | 2.11Gpm / 8.0Lpm | 2.65Gpm / 10Lpm |
| Max Pressure | 1450Psi / 100Bar | 1450Psi / 100Bar |
| Pump Model | DBCL-1510.5, Triplex brass | DBCL-1514, Triplex brass |
| Power And Type | 2KW, 4Pole, single phase | 2.5KW, 4Pole, single phase |
| Input Voltage | 220-240V, 50-60HZ | 220-240V, 50-60HZ |
| Max Outlet TEMP. | 194°F/90°C | 176°F/80°C |

JB SERIES 2600PSI Gas Engine High Pressure Washer

JB type frame equip with 6.5/7HP engine and SEMI-PRO axial pump

Semi-professional grade brass or aluminum forged axial pump, built with thermal protection and detergent injector. Performance proven gas engine, EU5 or EPA certified. Engine mount with anti-vibration rubber feet. Powder coating frame, easy push and move. Bolt on handle include with gun and hose hook. 10" solid wheel with plastic hub without bearing

Standard Accessories:

106.4mm x 8m thermal plastic hose, M22
Professional trigger gun, M22
20" stainless steel lance, 1/4" QD
5tips QD nozzles

Optional:

106.4 x 8m steel braided hose, M22
Forged brass or aluminum axial pump



FEATURES



| MODEL | DCAF-18/10JB | DCAC-18/10JB |
|------------------------|-------------------------------|-------------------|
| Max Pressure | 2600Psi / 179Bar | 2600Psi / 179Bar |
| Rated Flow | 2.7Gpm / 10.2Lpm | 2.7Gpm / 10.2Lpm |
| Pump Model | DAF-14065A, Aluminum manifold | DAC-14065A, Brass |
| Power And Type | 6.5hp/196cc, OHV | 6.5hp/196cc, OHV |
| Shipping Size | 67x41.5x55cm | 67x41.5x55cm |
| Shipping Weight | 36kgs | 36kgs |

LT SERIES 2600PSI Gas Engine High Pressure Washer

LT type frame equip with 6.5/7HP engine and SEMI-PRO axial pump

Standard Accessories:

106.4mm x 8m thermal plastic hose, M22
Professional trigger gun, M22
20" stainless steel lance, 1/4" QD
5tips QD nozzles

Optional:

106.4mm x 8m steel braided hose, M22
Forged brass or aluminum axial pump
Detergent tank



FEATURES



| MODEL | DCAF-18/10LT | DCAC-18/10LT |
|------------------------|----------------------|-------------------|
| Max Pressure | 2600Psi / 179Bar | 2600Psi / 179Bar |
| Rated Flow | 2.7Gpm / 10.2Lpm | 2.7Gpm / 10.2Lpm |
| Pump Model | DAF-14065A, Aluminum | DAC-14065A, Brass |
| Power And Type | 6.5hp/196cc, OHV | 6.5hp/196cc, OHV |
| Shipping Size | 56x56x63cm | 56x56x63cm |
| Shipping Weight | 36kgs | 36kgs |

JV SERIES 2600PSI Vertical Engine High Pressure Washer

JV type frame equip with 6.5/7HP VERTICAL engine and SEMI-PRO axial pump

Standard Accessories:

106.4mm x 8m thermal plastic hose, M22
Professional trigger gun, M22
20" stainless steel lance, 1/4" QD
4tips QD nozzles

Optional:

106.4mm x 8m steel braided hose, M22
Forged brass or aluminum axial pump



FEATURES



| MODEL | DCAF-18/10JV | DCAC-18/10JV |
|------------------------|-----------------------|-------------------|
| Max Pressure | 2600Psi / 179Bar | 2600Psi / 179Bar |
| Rated Flow | 2.7Gpm / 10.2Lpm | 2.7Gpm / 10.2Lpm |
| Pump Model | DAF-14065A, Aluminum | DAC-14065A, Brass |
| Power And Type | 6.5hp/196cc, Vertical | 6.5hp/196cc, OHV |
| Shipping Size | 67x41.5x55cm | 67x41.5x55cm |
| Shipping Weight | 38kgs | 38kgs |