

GRD SERIES

3200-3600PSI GEAR-REDUCTION

Electric start Gas Pressure Washer

D type frame equip with 9-13HP gas engine and GEAR-REDUCTION triplex pump

Commercial grade brass forged direct drive triplex pump, built with thermal protection and detergent injector. Performance proven gas engine, EU5 or EPA certified. Engine mount with anti-vebration rubber feet. Powder coating frame, all cover type, four wheel easy move. Folding handle, bolt on hook for gun and hose storage, onboard nozzle storage, 4x10" solid wheels.

Standard Accessories:

- 1D8mm x 10m steel braided hose, 3/8" QD
- Professional trigger gun, 3/8" QD Plug
- 20" stainless steel lance, 1/4" QD Plug outlet
- 5tips QD nozzles

Optional:

- Hose Reel
- Self Priming



FEATURES



Heavy-Commercial Grade
It is ideally suited for high-frequency use in large-scale or heavy-commercial cleaning scenarios.



Electric Starter
It uses electrical energy to drive mechanical structures, helping engine to start.



Engine Emission Approved
The gasoline engine equipped on the pressure washer has obtained EURO 5 Emission Certification.



Gearbox Reduction
By 2.18:1 ratio gear size set up, to reduce the input speed to the pump and reduce the wear and achieve longer use life.



20A/H Battery
To provide the instantaneous high-power electrical energy required for the electric starter to operation.



10" Solid Wheels
Rubber powder solid wheels are features bearing-free, impact resistance, wear resistance and maintenance free.



Integrated Anti-vibration
The inclined shock absorber pad Install under the pump and engine can efficiently disperse impact and vibration energy.

SPECIFICATIONS

MODEL	DCC-22/15GRD	DCD-24/17GRD
Max Pressure	3000Psi / 220Bar	3600Psi / 248Bar
Rated Flow	3.8Gpm / 14.35Lpm	4.5Gpm / 17Lpm
Pump Model	DBC-1812G4, Gear Reduction	DBD-1814G4, Gear Reduction
Power And Type	9.0hp/270cc, Electric Start	13hp/390cc, Electric Start
Shipping Size	82x55x66cm	82x55x66cm
Shipping Weight	63kgs	68kgs