


# DAA SERIES

**A** **VERSION**  
 Engine Direct Drive  
**HOLLOW SHAFT**  
**3/4in 19.05mm**  
**KEY 4.78mm**

**APPLICATIONS.** Consult us for more



## COMPONENTS



## TECHNICAL DATA

<b>Manifold:</b>	Brass forged	<b>Unloader:</b>	Integrated with manifold
<b>Housing:</b>	Die-cast aluminum alloy, anodized	<b>Unloader Port:</b>	Inlet 3/4" (BSP or NH), Outlet M22
<b>Wobble Plate:</b>	Forged steel alloy	<b>Oil Bath Capacity:</b>	150ml
<b>Plunger:</b>	Ceramic coating, precision grinded	<b>Oil Type:</b>	15W/40 Non-Detergent
<b>Packing:</b>	U type, high-low dual pressure packing	<b>Water Inlet Pressure:</b>	0-50psi/3.5bar
<b>Bearing:</b>	Dual thrust bearing	<b>Max Inlet Water Temp.</b>	≤ 50°C/122°F

MODEL	MAX FLOW		MAX PRESSURE		POWER INPUT	POWER SPEED	WEIGHT	SHIPPING SIZE
	GPM	LPM	PSI	BAR	HP	RPM	KG	CM
DAA-15063A	3.0	11.3	2800	193	6.5	3400	4.1	25x22.5x20
DAA-15054A	2.4	9.2	3000	206	6.5	3400	4.1	25x22.5x20

## OVERALL DIMENSION

