

DAC SERIES

A **VERSION**
 Engine Direct Drive
HOLLOW SHAFT
3/4in 19.05mm
KEY 4.78mm

APPLICATIONS. Consult us for more



COMPONENTS

MANIFOLD Brass Forged	HOUSING Aluminum Alloy	WOBBLE PLATE Forged Steel Alloy	BEARING Thrust Bearing	PLUNGER Coating Ceramic	PACKING U Type Dual Seal

TECHNICAL DATA

Manifold:	Brass forged	Unloader:	Integrated with manifold
Housing:	Die-cast aluminum alloy, anodized	Unloader Port:	Inlet 3/4" (BSP or NH), Outlet M22
Wobble Plate:	Forged steel alloy	Oil Bath Capacity:	120ml
Plunger:	Ceramic coating, precision grinded	Oil Type:	15W/40 Non-Detergent
Packing:	U type, high-low dual pressure packing	Water Inlet Pressure:	0-50psi/3.5bar
Bearing:	Dual thrust bearing	Max Inlet Water Temp.	≤ 50°C/122°F

MODEL	MAX FLOW		MAX PRESSURE		POWER INPUT	POWER SPEED	WEIGHT	SHIPPING SIZE
	GPM	LPM	PSI	BAR	HP	RPM	KG	CM
DAC-13071A	2.0	7.6	2400	166	6.5	3400	3.7	25x22.5x20
DAC-14067A	2.1	8.0	2600	179	6.5	3400	3.7	25x22.5x20
DAC-14071A	2.4	9.1	2600	179	6.5	3400	3.7	25x22.5x20

OVERALL DIMENSION

