

DBE SERIES


3 **VERSION**
 Motor Direct Drive
HOLLOW SHAFT
BORE 28mm
KEY 8.0mm



APPLICATIONS. Consult us for more



COMPONENTS



TECHNICAL DATA

Manifold:	Brass forged	Head Port:	Inlet 3/4", Outlet 3/8"
Crankcase:	Die-cast aluminum alloy, anodized	Unloader:	Banjo bolt, trap type
Connecting Rod:	One piece aluminum alloy	Unloader Port:	Outlet M22, Bypass 1/2"
Plunger:	Ceramic coating, precision grinded.	Oil Bath Capacity:	550ml (half level of oil gauge),
Packing:	U type, high-low dual pressure packing	Oil Type:	15W/40 Non-Detergent
Bearing:	Ball and needle bearing	Water Inlet Pressure:	0-50psi/3.5bar
Crankshaft:	Forged steel alloy, heat treatment, multiple process grinded	Max Inlet Water Temp.	≤ 50°C/122°F

MODEL	MAX FLOW		MAX PRESSURE		POWER INPUT	POWER SPEED	WEIGHT	SHIPPING SIZE
	GPM	LPM	PSI	BAR	KW	RPM	KG	CM
DBE-2218C3	8	30	1740	124	7.5	1450	10.7	36x32x29
DBE-2518C3	10	38	1450	100	7.5	1450	10.7	36x32x29

OVERALL DIMENSION

